

# Torridon HS Lite Drive Control Modules



---

Hot-Swap automation for SAS and SATA drives

---



## Reduce Time to Market

---

Cut time to market by 20% for new products by automating manual test procedures

## Reduce Capital Costs

---

Faster and more detailed testing with Torridon means fewer test systems are required in the lab

## Reduce Human Error

---

Removing human intervention during tests increases consistency and results in far fewer mistakes. Test scripting provides logging and 100% repeatability

## Increase Product Reliability

---

Advanced techniques, such as bounds testing and fault injection provide a higher level of confidence and reduced field returns

### **Torridon Drive Control Modules:**

The industry's first automated solution for hot-swap testing. Drive Modules vastly increase the speed of testing and introduce a level of repeatability and precision that is impossible during manual tests.

### **Complete Automation:**

Any test that requires manual intervention to pull or plug a drive can now be fully automated.

### **Simple Integration:**

The Torridon System works with your existing automated test setup and integrate with minimal effort. A simple command set allows for easy scripting. Quarch provides full support as standard while you get started

### **Who Can Benefit?**

Enclosure Manufacturers  
RAID Developers  
Storage System Integrators  
Drive Qualification Labs  
Silicon Manufacturers  
Software/Driver Designers

# Torridon SAS/SATA HS Lite Drive Control Modules

## Interface Specification

### Power

- ▶ Supplied from Torridon Interface Card or Array Controller

### Comms

- ▶ USART Serial - DB9
- ▶ USART Serial - RJ45(RS232D)
- ▶ Telnet (Via Array Controller)

## Drive Compatability

### Sizes

- ▶ 2.5" form factor (also compatible with 3.5" drives)

### Drive Connections

- ▶ SAS and keyed SATA options

### Types

- ▶ HDD, SSD, Tape

## Switching

### Switches

- ▶ High Speed FETs and RF Switches
- ▶ Low insertion loss, Flat frequency response

### Switched Pins

- ▶ All precharge, power and high speed SAS data pins. Vendor specific pins on request

## Timing Specification

### Timers

- ▶ 6 Independent timers for multi stage hot-swap

### Timing resolution

- ▶ 1mS

### Pin-bounce modes

- ▶ Not available on Lite control modules

### Manual Mode

- ▶ Full manual connection control for fault injection and bugged hardware generation

## Physical Dimensions

### QTL1301 (2.5" Module)

- ▶ 69.1mm x 15.mm
- ▶ Drive offset by 14mm

## Support and Utilities

Phone and email support direct to the engineers as standard

Tutorials, example scripts, PERL and C# code can be supplied

## Ordering Information

### QTL1301- 2.5" Form Factor

#### Single units

- ▶ Ideal for bench testing, debugging and evaluation
- ▶ Order with Torridon Interface Kit QTL1260

#### Multiple units

- ▶ Run from a Torridon Array Controller for synchronized testing of large disk arrays
- ▶ Order with Torridon Array Controller QTL1079

## Sales

### Quarch Technology Ltd

UK Sales / Technical Enquiries  
+44 1343 508 140  
enquiries@quarch.com

US Sales Office  
+1 617 245 0528  
us\_enquiries@quarch.com



<http://www.quarch.com>