

Torridon Ethernet Cable Pull Module



Hot-Swap automation for RJ-45 Ethernet cables



Reduce Time to Market

Cut time to market by 20% for new products by automating manual test procedures

Reduce Capital Costs

Faster and more detailed testing with Torridon means fewer test systems are required in the lab

Reduce Human Error

Removing human intervention during tests increases consistency and results in far fewer mistakes. Test scripting provides logging and 100% repeatability

Increase Product Reliability

Advanced techniques, such as bounds testing and fault injection provide a higher level of confidence and reduced field returns

Torridon Cable Pull Modules:

Automated solution for Cable Pull / Push and Fault Injection. Cable Pull Modules vastly reduce test duration and introduce a level of repeatability and precision that is impossible during manual tests.

Complete Automation:

Any test that requires manual intervention to pull or plug a cable can now be fully automated.

Simple Integration:

The Torridon System works with your existing automated test setup and integrates with minimal effort. A simple command set allows for easy scripting. Quarch provides full support as standard while you get started

Who Can Benefit?

Enclosure Manufacturers
Ethernet Developers
Storage System Integrators
Hardware Qualification Labs
Silicon Manufacturers
Software/Driver Designers

Torridon Ethernet Cable Pull Module

Interface Specification

Power

- ▶ Supplied from Torridon Interface Card or Array Controller

Comms

- ▶ USART Serial - DB9
- ▶ USART Serial - RJ45(RS232D)
- ▶ USB

Cable Compatability

Sizes

- ▶ Compatible with RJ-45 Ethernet cables.

Speeds

- ▶ Supports: 10/100/1000 Base T, and 10G base-T*

Switching

Switches

- ▶ High Speed RF switches
- ▶ Low insertion loss

Switched Pins

- ▶ All 8 RJ-45 Data Pins may be switched individually

Physical Dimensions

QTL1271

- ▶ Length 84.0 mm
- ▶ Width 63.5 mm
- ▶ Height 30.0 mm

Timing Specification

Timers

- ▶ 6 Independent timers for multi stage hot-swap

Timing resolution

- ▶ 1mS

Pin-bounce resolution

- ▶ 10uS

Pin-bounce modes

- ▶ Constant Frequency
- ▶ User defined 100 bit pattern

Manual Mode

- ▶ Full manual connection control for fault injection and bugged hardware generation

Glitching

Timing

- ▶ Glitch any combination of signals with pulses down to 50nS

Sequences

- ▶ Run glitches in sequences and PRBS patterns

Fault Injection

Ethernet Errors

- ▶ Create Data Errors
- ▶ Fault one side of a pair
- ▶ Fault entire pairs
- ▶ Create random disruption

Support and Utilities

Phone and email support direct to the engineers as standard

'TestMonkey' GUI for rapid test prototyping, script generation and bench testing

Ordering Information

QTL1271 - Single Unit

QTL1317 - Quad Unit in 19in Rack Panel

Single units

- ▶ Ideal for bench testing, debugging and evaluation

Multiple units

- ▶ Run from a Torridon Array Controller for synchronized testing of many cables

Quarch Technology Ltd

UK Sales / Technical Enquiries

+44 1343 508 140

enquiries@quarch.com

US Sales Office

+1 617 245 0528

us_enquiries@quarch.com

<http://www.quarch.com>

*For long cable lengths at 10G base-T, system performance should be verified before purchase